

Infrastructure as a Service (IaaS)

Roch Glitho, PhD

Full Professor


Ericsson / ENCQOR-5G Senior Industrial Research Chair

Cloud and Edge Computing for 5G and Beyond

My URL - http://users.encs.concordia.ca/~glitho



laaS



- Introduction
- Definitions and layers
- Challenges
- Resource Management
- Case Studies (XEN and Openstack)






Introduction





Introduction

Infrastructure as a Service (IaaS): immersed part II: Enduser perspective)





Introduction

Infrastructure as a Service (laaS): immersed part II: Enduser perspective)

Virtualized resources (CPU, memory, storage and eventually service substrates) used (on a pay per use basis) by applications

- Examples
- IBM Blue Cloud
- Amazon EC2





Definitions and layered view





Definition

"An laaS cloud enables on-demand provisioning of computational resources in the forms of virtual machines (VMs) deployed in a cloud provider data centres (such as Amazon's minimizing or even eliminating associated capital cost for cloud consumers .."

Reference 1

R. Moreno et al., Key Challenges in Cloud Computing: Enabling the Future Internet of Services, IEEE Internet Computing, July/August 2013

Note: A bit outdated since it does not include containers



Layering

(a) - Cloud consumers

laas consumers (e.g. PaaS, other clouds)

- (b) Cloud management layer
 - Overall laaS management
 - Interface with cloud consumers



Layering

- (c) Virtual infrastructure management layer Functionality includes:
 - Provides uniform / homogeneous view of virtualized resources
 - Virtualization platform independent
 - Handles VM life cycle
 - Handle addition / failure of physical resources
 - Server consolidation, high availability
- (d) Virtual machine management layer (i.e. hypervisors)



Layers




Figure 1. The cloud ecosystem for building private clouds. (a) Cloud consumers need flexible infrastructure on demand. (b) Cloud management provides remote and secure interfaces for creating, controlling, and monitoring virtualized resources on an infrastructure-as-a-service cloud. (c) Virtual infrastructure (VI) management provides primitives to schedule and manage VMs across multiple physical hosts. (d) VM managers provide simple primitives (start, stop, suspend) to manage VMs on a single host.

B. Sotomayor et al., Virtual Infrastructure Management in Private and Hybrid Clouds, IEEE Internet Computing, September/October 2009





Challenges





laaS Challenges




Figure 2. Cloud computing model for the future Internet of Services (IoS). Cloud technology enables the future IoS, and the infrastructure-as-a-service clouds represent this model's foundation.

R. Moreno et al., Key Challenges in Cloud Computing: Enabling the Future Internet of Services, IEEE Internet Computing, July/August 2013



Examples of laaS services

- Computing
- Storage
- Networking
- (Virtual) sensor/robot that can carry out given task(s)



Single laaS providers

- Dynamic service provisioning
 - Dynamic mapping of services onto resources via environment (e.g. virtualization platform, software library) independent interfaces
 - Require advanced SOA interfaces



Single laaS providers

- QoS and SLA negotiation
 - Require expressive mechanisms for QoS and SLA negotiation
 - Note: There are several negotiation mechanisms (e.g. offer / response. Offer/counter offer)



Single laaS providers

- Service scalability
- Service elasticity
- Service monitoring, billing and payment
- Context / situation awareness
 - Geographic restrictions
 - Service deployed close to a group of users
 - Legal restrictions



Aggregating laaS providers

- Service deployment across different providers
 - Hybrid clouds
 - Cloud brokering
 - Allow consumer to select most appropriate laaS providers
 - Publication / discovery



Aggregating laaS providers

- Interoperability
- Portability



Non functional challenges

Security

Availability, reliability and resilience

Energy efficiency






Resource Management





Resource Management



1 - The problem

 2 – VM migration (One of the techniques for tackling the problem)

 3 - On VM Migration based algorithms for laaS



- On virtual machine life cycle
 - Determine expected resources needed at deployment
 - Configure VM
 - Decide where to place it
 - Start VM
 - Track resource usage
 - Hot spot: Inadequate resource to meet performance
 - Cold spot: Overprovisioned resources

Note: Resource usage pattern is highly dependent on applications types



Overall problem

"Minimized resource utilization while meeting laaS users performance requirements"



- How could it be solved?
 - Server consolidation
 - Avoid cold spots on physical machines
 - Load balancing
 - Avoid discrepancy in resource usage on the different physical machines
 - Hot spot mitigation
 - Avoid conditions where a VM does not have enough resource to meet the performance requirements



How could it be solved (Reference 4)?




Figure 3. Load balancing and consolidation scenarios.



- How could it be solved?
 - Complementary / non mutually exclusive techniques
 - VM reconfiguration
 - Add / reduce resources
 - New VM instantiations
 - VM migration



- VM Migration
 - Process of transferring a VM with its state from one physical machine to another
 - Program transfer from one machine to another machine is not new, e.g.
 - Mobile agents (Late 90s, early 200s): Program than can start execution in a physical machine, suspend execution, then move to another machine to resume execution, then move again if necessay



- VM Migration
 - Techniques
 - Suspend and copy
 - Suspend a VM execution, copy state (memory + processor), then resume execution on target machine
 - Downtime proportional to VM size and network bandwidth available for transfer




- VM Migration
 - Techniques
 - Live migration (Pre-copy and post copy)
 - Minimize down time by either pre-copying or post copying state



- VM Migration
 - Techniques
 - Live migration (Pre-copy)
 - Pre-copy iteratively memory state to a set threshold (or until a condition is met) while still executing on host machine
 - Execution is suspended, processor state and remaining memory state are copied, and VM is restarted on target machine



On Virtual Machine Migration (Ref.5)





- Goals
 - Consolidation
 - Load balancing
 - Hot spot mitigation



- Questions
 - When to migrate?
 - Which VM to migrate?
 - Where to migrate the VM?



- Examples of constraints
 - Migration process overhead
 - Impact on applications
 - Degree of improvements in intended goals



- When to migrate?
 - Periodically, e.g.
 - data centres in several time zones
 - Hot spot
 - Excessive spare capacity
 - under-utilized VM migrated to free servers
 - VM migrated from overloaded servers
 - Load imbalance
 - Addition / removal of physical server



- Which VM to migrate?
 - overloaded VMs
 - Holistic approach
 - The overloaded VM is not always the best choice (Time for migrating it might be too high A less overloaded VM might be considered)
 - Affinity based
 - If 2 VMs are communicating, it might not make sense to move one and let the other due to delays



Virtual Machine Migration Based Algorithms

- Where to migrate?
 - Available resource capacity
 - Affinity






Case Studies





Case studies



Case study 1: XEN (VM Management solution)

Case study 2: Openstack (cloud management solution)



laaS Layers




Figure 1. The cloud ecosystem for building private clouds. (a) Cloud consumers need flexible infrastructure on demand. (b) Cloud management provides remote and secure interfaces for creating, controlling, and monitoring virtualized resources on an infrastructure-as-a-service cloud. (c) Virtual infrastructure (VI) management provides primitives to schedule and manage VMs across multiple physical hosts. (d) VM managers provide simple primitives (start, stop, suspend) to manage VMs on a single host.



XEN



P. Barham et al., Xen and the Art of Virtualization, Proceeding SOSP '03 Proceedings of the nineteenth ACM symposium on Operating systems principles, Pages 164-177



Design goals

- Unmodified application binaries
- Multi application operating systems
- Para-virtualization (instead of binary translations)



Architecture (Ref. 6)




Figure 1: The structure of a machine running the Xen hypervisor, hosting a number of different guest operating systems, including *Domain0* running control software in a XenoLinux environment.





T. Rosado and J. Bernardino, An Overview of Openstack, Proceeding IDEAS '14 Proceedings of the 18th International Database Engineering & Applications Symposium

On Cloud Management Solutions

- Highest level of abstraction towards consumers (e.g. Paas)
- Monolithic blocks integrating virtual infrastructure managers in most cases
 - No clean interface with virtual infrastructure managers



Openstack (A non comprehensive view – Reference 7)




Figure 1 - Openstack conceptual architecture

- Open source combination of related software projects, with a subset shown on previous figure:
- Some examples
 - Computing
 - Nova
 - Independence of specific VMs (e.g. XEN, KVM, VMWare)
 - Glance
 - Image service
 - Networking
 - Neutron



- Storing
 - Swift
 - Highly available distributed object store
 - Cinder
 - Persistent block storage
 - VM back up by working with Swift



- Shared services
 - Ceilometer
 - metering
 - Keystone
 - Identity management
 - Horizon
 - User interface for cloud infrastructure management



Examples of services which do not appear on the figure

- Orchestration
 - Heat
- Bare metal provisioning
 - Ironic

Note: Bare metal provisioning in Openstack world means giving access to the bare hardware with no hypervisor

- No virtualization
- Single tenant !!!
 - » Might be useful in cloud environment if one wishes to use a specific specialized piece of hardware dedicated to a single tenant



The End





